

eBOX511-820-FL

Fanless Embedded System with Intel® Atom™ Processor Z510/Z530 up to 1.6 GHz and Wide Range DC-in



Front view



Rear view

Specifications

Standard Color	Silver-Black
Construction	Aluminum extrusion and heavy-duty steel
CPU	Intel® Atom™ processor Z510 (1.1 GHz) or Z530 (1.6 GHz)
System Memory	1 x 200-pin DDR2 SODIMM max. up to 2 GB
Chipset	Intel® US15W core logic
BIOS	Phoenix-Award
System I/O Outlet	2 x RS-232 (COM 1/2) 1 x VGA 1 x Audio (Line-out/Mic-in) 1 x PS/2 keyboard/mouse 1 x 10/100/1000Mbps Ethernet 4 x USB 2.0 1 x DC-inlet
Watchdog Timer	255 levels, 1 ~ 255 sec.
Storage	Supports 1 x CompactFlash™
Expansion Interface	N/A
System Indicator	1 x green LED for system power-on 1 x orange LED for HDD active
Power Supply	25W wide-range DC-in (10Vbc ~ 30Vbc)
Operating Temperature	0°C ~ +50°C (32°F ~ 122°F) (with W.T. CF)
Storage Temperature	-20°C ~ +80°C (-4°F ~ +176°F)
Humidity	10% ~ 90%, no-condensing
Dimensions	132 mm (5.19") (W) x 95.4 mm (3.75") (D) x 47.5 mm (1.87") (H)
Weight (net/gross)	0.6 kg (1.32 lb)/1.2 kg (2.64 lb)
Certification	CE
EOS Support	XPE, CE, Linux

* XPE: Windows® XP Embedded

Packing List

1 x quick manual
1 x driver CD
1 x Y cable for PS/2 keyboard/mouse
1 x screw pack
4 x foot pad

Features



- Supports Intel® Atom™ processor Z510 (1.1 GHz) or Z530 (1.6 GHz)
- Intel® US15W core logic chipset
- Ultra slim and power-efficient design
- Supports 4 USB 2.0 ports and 2 COM port
- Supports one 10/100/1000Mbps Ethernet port
- One CompactFlash™
- DC-in wide range



Ordering Information

Standard	
eBOX511-820-FL 1.1G	Fanless embedded system with Intel® Atom™ processor 1.1 GHz and wide range DC-in
eBOX511-820-FL 1.6G	Fanless embedded system with Intel® Atom™ processor 1.6 GHz and wide range DC-in
Optional	
DDR2 SODIMM	512 MB ~ 2 GB
CompactFlash™	1 GB ~ 16 GB
Din rail kit	
Wall mount kit	
VESA mount kit	
Power cord	

*Specifications and certifications are limited to optional.

Dimensions

