

2-port 10GbE PoE PCI Express Card

Features

- Intel® Ethernet Controller X550-AT2, up to 10 Gbps data rate
- Supports 15.5KB Jumbo Frame and IEEE 1588
- Compliant with IEEE802.3at to deliver 25.5W per port
- PCI Express x4 compliant
- PoE power on/off via Power Manager software and API
- Operating temperature range from 0°C to 55°C





Introduction

The AX92324 is a dual-port 10GbE PEI Express card based on the Intel® Ethernet Controller X550-AT2. To meet the demands of the next-generation 10GbE cameras with high resolution and high-speed transmission over one single Ethernet cable, the AX92324 $\,$ features the combination of 10GbE and IEEE802.3at compliant PoE capabilities. It also supports PoE power on/off and power budget settings via management software or API. The AX92324 is suitable for high bandwidth, high-speed transmission and low latency requirements for machine vision, intelligent surveillance and network applications.

Specifications

| <u> </u> | |
|-------------------------|---|
| Ethernet Communications | |
| Ethernet Port | 2 GbE LANs with Intel® X550-AT2 controller; supports 15.5KB jumbo frame and IEEE 1588 |
| PoE Capability | IEEE 802.3at compliant; each port delivers up to 30W at 54 VDC |
| Data Rate | 10Gbps/*5Gbps/*2.5Gbps/1Gbps/100Mbps (*Linux only) |
| Port Connector | 8-pin RJ-45 |
| Power Requirements | |
| Input Voltage | 12 VDC or 24 VDC* (*24VDC ATX power connector is used for Axiomtek's system only) |
| Overload Protection | Yes |
| Connection | 6-pin ATX power connector |
| Output PoE Power | Max. 20W w/ PCIe slot Max. 60W w/ 6-pin ATX power connector |
| Power Requirements | Power from PCle slot (max. 20W PoE power output) 2.1A @ +12V 1.2A @ +3.3V Power from ATX power connector (max. 60W PoE power output) 6A @ +12V or 3A @ +24V 1.2A @ +3.3V (from PCle slot) |
| General Specifications | <u> </u> |
| Bus Type | PCI Express x4 |
| Operating Temperature | 0°C to +55°C (+32°F to +131°F) (with air flow) |
| Storage Temperature | -20°C to +80°C (-4°F to +176°F) |
| Humidity | 10% to 95%, non-condensing |
| Dimensions (W x D) | 168 x 111 mm |
| OS Support | Windows® 7/10, Linux |

Ordering Information

| AX92324-PoE (P/N: E392324100) | 2-port 10GbE PCIe card with PoE |
|--|--|
| AX92324-w/o PoE (P/N: E392324101) | 2-port 10GbE PCle card |
| PoE Power Cable (P/N: 59492320700E) | 4P 3.0/6P 4.2, L=10 cm (only used with IPC962/IPC964/IPC974) |