

SSK515 (CUBE Kiosk) NEW

15.6" Self-Service Kiosk with Intel® Smart Display Module (SDM-L) CPU Card, 10-point PCAP Touch, 2D Barcode Scanner, Thermal Printer, and NFC

Features

- 15.6" Full HD LCD with 10 point PCAP touch (300 nits brightness)
- Supports Intel® Smart Display Module Large (Intel® SDM-L) with Intel® Core™ i5/i3 or Intel® Celeron® processor (Whiskey Lake)
- Equipped with illuminating status LEDs
- Modular design
- All-in-one and slim body design with under 90 mm thickness
- Supports wall mount and counter top stand



Specifications

Front Bezel	IP54, metallic front bezel	
LCD Panel	Display Type	15.6" FHD TFT LCD
	Brightness (cd/m ²)	300 nits
	Resolution	1920 (H) x 1080 (V)
	Aspect Ratio	16:9
Main System	Intel® SDM Large (SDM-L, 175 x 100 mm)	
I/O Connector	SDM-L I/O	1 x Power button with LED
		1 x GbE LAN
		4 x USB 3.0 Type A
		1 x Audio output
		1 x Microphone input
Touchscreen	10-point projected capacitive touch with direct bonding	
LED Light Bar	1 LED light bar in support of 256 colors	
Power Supply	150W DC adapter	
Power Consumption	Average 90W	
Dimensions	308 mm (14.96") (W) x 85 mm (3.34") (D) x 471 mm (18.54") (H)	
Weight (net/gross)	9.4 kg (20.7 lb)/14.5 kg (31.9 lb)	
Operating Temperature	0°C to +40°C (+32°F to +104°F)	
Operating Humidity	20% - 80%, non-condensing	
Certifications	CE, FCC Class A	

CPU Card Selection: SDM500-L

CPU	Intel® Core™ i5-8365UE processor, 1.6GHz	
	Intel® Core™ i3-8145UE processor, 1.6GHz	
	Intel® Celeron® 4305UE processor, 2.0GHz	
System Memory	2 x 260-pin DDR4-2400 SO-DIMM slot, up to 64GB	
BIOS	AMI UEFI BIOS	
Storage	1 x M.2 Key B 2280 slot	
Watchdog Timer	255 levels, 0 to 255 sec.	
Onboard Graphics	Intel® UHD Graphics 620/610 (depends on CPU card)	
I/O Connector	Rear Side	1 x Power button with LED
	(depends on SDM I/O)	1 x GbE LAN
		2 x USB 3.0 Type A
		1 x Audio output
		1 x Microphone input
Expansion Interface	1 x M.2 Key E 2230 slot (for the Wi-Fi/4G LTE)	

Ordering Information

Standard	
SSK515-CLB-TBF1	15.6 FHD with PCAP touch slim bezel panel with SDM-L, Intel® Celeron® 4305UE, 4GB memory, 64GB M.2 SSD, LED light bar, thermal printer, 2D barcode scanner, NFC, GbE LAN, 4 USB 3.0, 2 speakers, 1 Mic-in, 1 Line-out, and 1 DC Jack
SSK515-I3B-TBF1	15.6 FHD with PCAP touch slim bezel panel with SDM-L, Intel® Core™ i3 8145UE processor, 4GB memory, 64GB M.2 SSD, LED light bar, thermal printer, 2D barcode scanner, NFC, 1 LAN, 4 USB 3.0, 2 speakers, Mic-in & Line-out, and DC Jack
SSK515-I5B-TBF1	15.6 FHD with PCAP touch slim bezel panel with SDM-L, Intel® Core™ i3 8365UE, 4GB memory, 64GB M.2 SSD, LED light bar, thermal printer, 2D barcode scanner, NFC, GbE LAN, 4 USB 3.0, 2 speakers, Mic-in & Line-out and DC Jack

