

SSK721

21.5" Self-Service Kiosk with 9th/8th Intel® Core™ i7/i5/i3 Processor



Features

- 21.5" Full-HD touch panel with wide viewing angle
- Cash payment: bill acceptor, note dispenser, coin acceptor
- Cashless payment: barcode scanner, RFID reader, EFT holder
- Thermal printer



Multi-touch



RFID/NFC readers



Thermal tickets printer



POS machine



QR code scanner



1. 21.5" Touch Panel
2. Note Dispenser
3. Changes Chamber
4. Speaker
5. Handle
6. Door Lock

7. EFT Holder (reserved)
8. Coin Acceptor / Sorter / Hopper
9. Bill Acceptor
10. Barcode Scanner
11. RFID Reader
12. Thermal Printer

Specifications

LCD Panel	Display Type	21.5" FHD TFT LCD
	Brightness (cd/m ²)	250 nits
	Resolution	1920 (H) x 1080 (V)
	Aspect Ratio	16:9
Main System	Mano522	Mini-ITX SBC with LGA1151 9th/8th Gen Intel® Core™ i7/i5/i3 processor (up to 65W)
	Memory	4G DDR4-2666
	Storage	128G mSATA
Cash Payment	Bill Acceptor	iCT XBA-mini (600 notes)
	Note Dispenser	iCT NDE1000 (500 notes)
	Coin Acceptor	iCT UCA series (3 coins/sec.)
	Coin Sorter	iCT coin sorter (3 coins/sec.)
	Coin Hopper	iCT Mini Hopper (500 - 1000 coins)
Peripheral	Barcode Scanner	Honeywell
	RFID Reader	Mafire 13.56 MHz, ISO14443A card read
	EFT	EFT holder
	Printer	2"/3" thermal printer
Touchscreen	10-point projected capacitive touch	
Speaker	2 x 3W speaker	

Specifications

Power Supply	110-240V DC-in
Power Consumption	Average 200W
Dimensions	664.3 mm (26.2") (W) x 436.1 mm (17.2") (D) x 833.8 mm (32.8") (H)
Weight (net)	72 kg (159 lb)
Operating Temperature	0°C to +40°C (+32°F to +104°F)
Operating Humidity	30% - 80%, non-condensing
Main System	
CPU	Intel® Core™ i3-8100T processor, 3.1GHz
System Memory	2 x 260-pin DDR4-2666/2400 SO-DIMM slot, up to 64GB
BIOS	AMI
Storage	1 x mSATA
Watchdog Timer	255 levels, 1 to 255 sec.
Onboard Graphics	Intel® integrated Gfx graphic engine
Expansion Interface	1 x M.2 Key E 2230 slot for Wi-Fi/Bluetooth

Dimensions

